



THE HARD DUTY LINE

THE REAL "WORK-HORSE" FOR YOUR TYRE SHOP!!

NEW

SX228 PRO LNL



RACING SUPER-AUTOMATIC LEVER - NO LEVER TILT BACK TYRE CHANGER WITH DUAL ASSIST ARM AND POWER X



Suitable for Tubeless tyre bead seating system (optional)



MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version



COMING SOON...

Discover on our website!



5 YEAR WARRANTY ON POWERX
5 YEAR WARRANTY ON GEARBOX

100% Made in Italy



Robotic pipe for operating arm positioning/lock

Tools Storage Box (standard)

Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm

Tyre inflation by pedal (standard)

Lever-No-Lever tyre mounting / demounting system [Giuliano Patent], (standard).



Available in:

- Blue Trim
- Black Trim
- Red Trim

HP4 DUAL ASSIST ARM (standard):

- Bead Pressing Roller
- Bead Lifting Roller
- Bead Pressing Pad

POWER X grants double (uniform) clamping power on jaws, and an almost **endless durability** and **reliability** of your turntable!!!

Tabletop thickness 14 mm with **POWER X** four cylinders clamping system [Giuliano Patent].

Reinforced Chassis and Tower

"Easy Access" extractable pedal box for quick service

Double rotation speed by pedal

LNL SYSTEM [Patented] can work either with or without bead lifting lever



"NO LEVER" MODE



"LEVER" MODE



Control lever to manage movements of the tool.

"LEVER" & "NO LEVER" Mode control handle



Bead breaker **double effect Cylinder** \varnothing 200 mm.

Adjustable bead breaker shovel stroke.



Patented **PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.

STANDARD FEATURES

Rim clamping from outside	10" - 27"
Rim clamping from inside	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph-2 speed 220V-1ph/220V-1ph-2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	380 kg
Max. overall dimensions	1590x1930x2160 mm

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

Bead lifting lever • Lube paste bucket and Brush • Plastic protectors for LNL mounting/demounting tool • 2 Protectors for bead breaker shovel • Jaw protectors for alloy rims • Lubricator + Pressure regulator • Bucket support